

Type	BCI Group Size	Volt	AH / 5HR	AH / 20HR	Capacity Minutes		Cranking Performance		Length		Width		Height		Total Height		Weight (Approx.)		Terminal Type	Pallet Qty
					@25 Amps	@75 Amps	CCA @0°F	CA @32°F	mm	in	mm	in	mm	in	mm	in	kg	pound		
DC1150-2	903/L16	2	945	1150	1220	1275	2235	658	295.0	12.0	179.0	7.0	404.0	16.0	411.0	16.0	58.0	127.0	M10	22
DC200-6	27	6	165	200	400	100	/	/	306.0	12.0	169.0	7.0	220.0	9.0	226.0	9.0	30.0	66.0	M8	36
DC220-6	27	6	180	220	425	112	/	/	306.0	12.0	174.0	7.0	220.0	9.0	226.0	9.0	33.0	72.0	M8	36
DC224-6A	GC2	6	179	224	441	113	/	/	260.0	10.0	180.0	7.0	245.0	10.0	251.0	10.0	30.0	66.0	M8	42
DC224-6B	GC2	6	179	224	441	113	/	/	260.0	10.0	180.0	7.0	263.0	10.0	263.0	10.0	30.0	66.0	M8	42
DC245-6	(DIN)	6	198	245	457	120	/	/	244.0	10.0	190.0	7.0	275.0	11.0	275.0	11.0	32.0	71.0	AP	30
DC250-6	GC2	6	204	250	531	135	/	/	262.0	10.0	181.0	7.0	266.0	10.0	272.0	11.0	35.0	76.0	M8	28
DC335-6	902/J305	6	274	335	751	184	/	/	295.0	12.0	178.0	7.0	346.0	14.0	366.0	14.0	48.0	105.0	DT	22
DC400-6	L16	6	340	415	885	229	/	/	295.0	12.0	178.0	7.0	404.0	16.0	424.0	17.0	56.0	123.0	DT	22
DC160-8A	GC8	8	131	160	315	112 @56Amps	/	/	260.0	10.0	182.0	7.0	268.0	11.0	272.0	11.0	32.0	70.0	M8	28
DC160-8B	GC8	8	131	160	315	112 @56Amps	/	/	260.0	10.0	182.0	7.0	288.0	11.0	288.0	11.0	32.0	70.0	M8	28
DC180-8A	GC8	8	147.5	180	335	125 @56Amps	/	/	260.0	10.0	182.0	7.0	268.0	11.0	272.0	11.0	37.0	81.0	M8	28
DC180-8B	GC8	8	147.5	180	335	125 @56Amps	/	/	260.0	10.0	182.0	7.0	288.0	11.0	288.0	11.0	37.0	81.0	M8	28
DC200-8	GC8H	8	164	200	390	140 @56Amps	/	/	260.0	10.0	182.0	7.0	295.0	12.0	299.0	12.0	40.0	88.0	M8	28
DC7-12	N/A	12	/	7	/	/	/	/	151.0	6.0	65.0	3.0	95.0	4.0	101.0	4.0	3.0	6.0	F1	420
DC10-12	N/A	12	/	10	/	/	/	/	151.0	6.0	65.0	3.0	111.0	4.4	117.0	4.6	3.3	7.3	F1	336
DC12-12	N/A	12	/	12	/	/	/	/	151.0	6.0	99.0	4.0	95.0	4.0	101.0	4.0	4.0	9.0	F1	264
DC17-12	N/A	12	/	17	20	/	120	148	181.0	7.0	77.0	3.0	167.0	7.0	167.0	7.0	6.0	14.0	M5	192
DC20-12	N/A	12	16.5	20	23	/	135	165	181.0	7.0	77.0	3.0	167.0	7.0	167.0	7.0	6.0	14.0	M5	192
DC24-12	N/A	12	19.8	24	27	/	160	195	167.0	7.0	175.0	7.0	125.0	5.0	125.0	5.0	9.0	20.0	M5	120
DC26-12A	N/A	12	21.3	26	30	/	165	195	166.0	6.5	126.0	5.0	174.0	6.8	174.0	6.8	10.0	22.0	M5	114
DC26-12B	N/A	12	21.3	26	27.6	/	165	200	165.0	6.5	176.0	7.0	125.0	5.0	125.0	5.0	9.4	20.7	M6	120
DC35-12A	U1	12	29	35	52	/	190	230	196.0	8.0	131.0	5.0	155.0	6.0	167.0	7.0	12.0	25.0	M6	108
DC35-12B	U1	12	29	35	52	/	190	230	196.0	8.0	131.0	5.0	167.0	7.0	180.0	7.0	12.0	25.0	F25	108
DC38-12	U1L	12	31	38	52	/	265	315	198.0	7.8	166.0	6.5	174.0	6.9	174.0	6.9	13.3	29.3	M6	96
DC40-12	U1L	12	32.8	40	53	/	275	320	198.0	7.8	166.0	6.5	174.0	6.9	174.0	6.9	13.4	29.5	M6	96
DC50-12A	(DIN) L2	12	41	50	85	17	440	575	241.0	9.5	175.0	6.9	190.0	7.5	190.0	7.5	18.5	40.8	AP	64
DC50-12B	U1L	12	40	50	53	/	350	400	198.0	7.8	166.0	6.5	171.0	6.7	171.0	6.7	14.5	32.0	M6	96
DC55-12	22NF	12	45	55	96	21	400	480	229.0	9.0	138.0	5.4	208.0	8.2	212.0	8.3	17.6	38.8	M6	63
DC60-12A	48	12	49.2	60	95	24	410	485	265.0	10.4	166.0	6.5	188.0	7.4	188.0	7.4	20.7	45.6	AP	45
DC60-12B	(DIN) L3	12	49.2	60	105	24	510	670	278.0	10.9	175.0	6.9	190.0	7.5	190.0	7.5	22.0	48.5	AP	48
DC65-12A	93	12	53.3	65	100	28	430	510	351.0	13.8	167.0	6.6	176.0	6.9	176.0	6.9	23.6	52.0	M6	48
DC70-12	24	12	57.5	70	115	31	450	540	260.0	10.2	169.0	6.7	211.0	8.3	215.0	8.5	23.8	52.5	M6	48
DC79-12	27	12	64	79	125	31	600	710	307.0	12.0	169.0	6.7	211.0	8.0	215.0	8.0	27.0	58.4	AP	36
DC80-12	L5	12	65.5	80	142	32	630	756	353.0	13.9	175.0	6.9	190.0	7.5	190.0	7.5	26.8	59.1	M6	36
DC85-12	24	12	70	85	148	34	510	600	260.0	10.2	169.0	6.7	211.0	8.3	215.0	8.5	25.1	55.3	M6	48
DC90-12	27	12	74	90	140	38	530	630	307.0	12.1	169.0	6.7	211.0	8.3	215.0	8.5	28.7	63.3	M6	36
DC105-12	27	12	86	105	175	43	550	660	307.0	12.1	169.0	6.7	211.0	8.3	215.0	8.5	30.2	66.6	M6	36
DC115-12A	31	12	91	115	200	45	600	710	328.0	12.9	172.0	6.8	214.0	8.4	220.0	8.7	32.7	72.1	M8	36
DC115-12B	31	12	91	115	200	45	605	720	331.0	13.0	175.0	6.9	214.0	8.4	218.0	8.6	32.9	72.5	M8	36
DC120-12A	N/A	12	98	120	230	52	750	900	407.0	16.0	174.0	6.9	210.0	8.3	240.0	9.4	38.2	84.2	M8	27
DC120-12B	31	12	91	120	230	45	605	720	331.0	13.0	175.0	6.9	214.0	8.4	218.0	8.6	36.0	79.4	M8	36
DC120-12C	N/A	12	98	120	232	56	750	900	341.0	13.4	172.0	6.8	267.0	10.5	283.0	11.1	38.7	85.3	AP	24
DC120-12D	(DIN)	12	98	120	232	56	750	900	260.0	10.0	180.0	11.6	297.0	11.6	301.0	11.8	35.6	78.5	M8	28
DC140-12	(DIN)	12	115	130	260	62	795	950	344.0	13.5	172.0	6.8	280.0	11.0	283.0	11.1	43.1	95.0	AP	24
DC145-12	N/A	12	122	145	279	86	820	975	341.0	13.4	173.0	6.8	281.0	11.1	287.0	11.3	44.3	97.7	M8	24
DC150-12	GC12	12	123	150	295	80	900	1.05	327.0	12.9	182.0	7.2	269.0	10.6	273.0	10.7	42.6	93.9	M8	24
DC160-12	N/A	12	130	160	300	82	910	1.07	484.0	19.1	171.0	6.7	241.0	9.5	241.0	9.5	45.5	100.3	M8	24
DC180-12	4D	12	147.5	180	350	85	/	/	530.0	20.9	209.0	8.2	214.0	8.4	218.0	8.6	56.8	125.2	M8	21
DC210-12	4D	12	172	210	400	105	/	/	530.0	20.9	209.0	8.2	214.0	8.4	218.0	8.6	60.5	133.4	M8	21
DC215-12	921/185	12	172	215	420	110	/	/	381.0	15.0	178.0	7.0	351.0	13.8	371.0	14.6	60.0	132.3	DT	20
DC220-12	4D	12	172	220	415	110	/	/	522.0	20.6	242.0	9.5	218.0	8.6	222.0	8.7	66.5	146.6	M8	18
DC240-12	8D	12	197	240	520	135	/	/	520.0	20.5	269.0	10.6	204.0	8.0	208.0	8.2	75.2	165.8	M8	12
DC260-12	8D	12	213	260	578	145	/	/	521.0	20.5	269.0	10.6	220.0	8.7	224.0	8.8	78.2	172.4	M8	12