

Fullriver Type	DIN Size	Nominal Voltage V	C ₁₀₀ 1.80 V/C 25°C Ah	C ₇₂ 1.80 V/C 25°C Ah	C ₁₀ 1.80V/C 25°C Ah	Length (L) max. mm	Width (W) max. mm	Height (H1) max. mm	Height (H2) max. mm	Weight approx. Kg	Terminal	Pole pairs
2V Fullriver Solar-Gel Battery												
FSG280-2	4OPZV200	2	282	270	220	103	206	355	380	17.4	M10	1
FSG350-2	5OPZV250	2	352	340	275	124	206	355	380	21.1	M10	1
FSG420-2	6OPZV300	2	422	410	330	145	206	355	380	24.6	M10	1
FSG450-2	5OPZV350	2	450	435	310	124	206	471	496	24.4	M10	1
FSG565-2	5OPZV350	2	566	550	390	124	206	471	496	29.1	M10	1
FSG680-2	6OPZV420	2	679	665	468	145	206	471	496	34.1	M10	1
FSG790-2	7OPZV490	2	792	775	546	166	206	471	496	38.4	M10	1
FSG860-2	6OPZV600	2	862	845	616	145	206	646	671	42.4	M10	1
FSG1000-2	6OPZV600	2	999	979	666	145	206	646	671	50.3	M10	1
FSG1100-2	8OPZV800	2	1103	1081	777	210	191	646	671	58.3	M10	2
FSG1220-2	11OPZV770	2	1225	1200	845	210	254	471	496	61.2	M10	1
FSG1330-2	8OPZV800	2	1332	1302	888	210	191	646	671	67.1	M10	2
FSG1660-2	10OPZV1000	2	1665	1632	1110	210	233	646	671	82.5	M10	2
FSG1850-2	12OPZV1200	2	1854	1815	1236	210	275	646	671	97.6	M10	2
FSG2020-2	12OPZV1500	2	2025	1985	1500	210	275	796	821	116	M10	2
FSG2360-2	16OPZV2000	2	2360	2315	1750	212	397	772	797	145	M10	3
FSG2600-2	16OPZV2000	2	2600	2540	2000	212	397	772	797	161	M10	3
FSG2880-2	16OPZV2000	2	2880	2820	2250	212	397	772	797	172	M10	3
FSG3370-2	18OPZV2500	2	3375	3300	2500	212	487	772	797	201	M10	4
FSG3570-2	18OPZV2500	2	3570	3500	2750	212	487	772	797	212	M10	4
FSG4050-2	24OPZV3000	2	4050	3965	3000	212	576	772	797	240	M10	4
FSG4220-2	24OPZV3000	2	4220	4140	3250	212	576	772	797	251	M10	4
12V Fullriver Front Access Terminal Gel Battery												
FTG105-12	N/A	12	125	-	103	394	125	292	292	38.2	M8	1
FTG160-12	N/A	12	190	-	160	560	125	317	317	58.1	M8	1